

EFS Catalogue

TOYOTA LANDCRUISER V8 HVDJ79R SINGLE AND DUAL

CAB CHASSIS 2007 ON - 50mm Lift

www.efs4wd.com.au



Suspension	Part Type	Part	Sub Brand	Qty	Notes
Front	Shock Absorbers	36-5546	ELITE	2	EFS Elite
Front	Shock Absorbers	37-6004	XTR	2	EFS XTR
Front	Coil Springs	TLC-103CE	EFS	1 PR	Up to 60 kg Load bearing accessories.
Front	Coil Springs	TLC-103E	EFS	1 PR	60 kg to 100kg of Load Bearing Accessories.
Front	Coil Springs	TLC-103HDE	EFS	1 PR	100 to 130 kg of Load Bearing Accessories.
Front	ABS Wire Relocation Kit Toyota	10-1080	EFS	1	ABS extension bracket. For ABS models only
Front	Sway Bar Spacer Toyota Landcruiser	10-1081	EFS	1	Front sway bar 25mm spacer blocks
Front	Steering Damper	SD4025	ENFORCER	1	
Front	Steering Damper	35-4025	EXTREME	1	EFS Extreme. Suitable for large tyre sizes
Front	Adjustable Panhard Rod	10-1068	EFS	1	
Front	Castor Bush Kit	10-1004	EFS	1	2 degree offset castor bush kit
Front	Coil Spacer	10-1029	EFS	2	10mm Spacer - for trimming or raising vehicle height.
Front	Radius Arm Bushes	10-1041	EFS	1	Radius Arm to chassis mount
Rear	Shock Absorbers	36-5548	ELITE	2	EFS Elite
Rear	Shock Absorbers	37-6005	XTR	2	EFS XTR
Rear	Leaf Springs	TLC-20-10	EFS	2	Constant 300kg.
Rear	Leaf Springs	TLC-20P	EFS	2	Parabolic Spring - Constant 450kg - Mining & Constant Load Applications. Not recommended for extreme offroad use due to clearance issues with second stage leaf.
Rear	Leaf Springs	TLC-21-10	EFS	2	Constant 400kg.
Rear	Leaf Springs	TLC-79G	EFS	2	Constant 600kg.
Rear	Leaf Springs	TLC-79GHD	EFS	2	Constant 700kg. Must use C417 Ubolt
Rear	Spacer Block Brake Valve 79 Series	10-1009	EFS	1	Brake proportioning valve spacer block
Rear	Bush Kit	UK742	EFS	1	Can be used as OEM replacement bush kit for Vehicles up to 07/2009. For 07/2009 on vehicles, must be installed with GR356 and GR358 greasable shackles and pins, sleeve to be removed. Use lithium or silicon based grease only
Rear	Ubolts	C416	EFS	4	
Rear	Ubolts	C417	EFS	4	Must be used when installing TLC-79GHD
Rear	Fixed Shackle Pin	GR356	EFS	2	Use UK742 bush kit - Remove sleeve before installing Shackle Pin.
Rear	Swing Shackles	GR358	EFS	2	Use UK742 bush kit - Remove sleeve before installing Swing Shackles.
Rear	Air bags	85320R	EFS	1	Bellow type bag - For use with Raised Suspension.